

**NATIONAL GAMES SECRETARIAT
SQUASH COURT-SPORTS ITEMS
SPECIFICATION AND SCHEDULE OF QUANTITIES**

SECTION - 8

Part 1 Supply of materials

S/No	Description of item (with brief specification and reference to Book of specification)	Qty	Unit	In Figures In USD/ EURO	Rates in Words In USD/EURO	Amount (Rs)
1.0	<p>Maple Wood Flooring :- Providing MAPLE HARDWOOD FLOORING: World Squash Federation Certified Maple Hardwood Sports Floors In Size 20 - 22 mm x 63.5mm/83mm Tongue & Groove 38mm x 63.5mm x 1.22m Treated Sleepers installed at 9" (23cm) distance 19mm Pads Sanded, Kiln & Dried Treated Warranty 25 years of flooring. The specifications of the above squash court flooring are as under:</p> <ol style="list-style-type: none"> 1. 6 mil Polyethylene shall be laid on the IPS surface as vapor barrier 2. Sleepers – 70mm X 40mm X 1.22m Fir, Spruce or Pine, treated with Borate shall be installed at 9" distance. 3. These sleepers have 19mm Pads properly stapled at 10" distance. These Pads are four conical Thermal Rubber (TPR) with reverse cavity. 4. Northern America Maple Strips in size 20mm x 63.5mm/83mm, in Random Lengths of 300mm – 1830mm, tongue & groove, Kiln & Dried Treated shall be installed the sleeper. 5. The floor thus laid shall be machine sanded with drum sander – one time – i.e. coarse grade (60grit) sandpaper to leave a "nap" on the floor for non-slipperiness. The floor shall not be sealed. 6. Thereafter game lines shall be applied resulting in warranty for the flooring for 25 years. <p>The floor must be approved from World Squash Federation, complete in all respect to the entire satisfaction of Engineer-in-Charge.</p>	274	sqm			
2.0	<p>Rear Glass Wall :- Providing Rear Glass Wall World Squash Federation Certified Championship Back Glass Wall for Squash Court complete with all Hardware and Installation. *Glass rear Wall with door. * ½" thick tempered glass and complete with all extruded aluminum hardware, powdercoated brilliant white, fins, games lines and silicone. Door size to be 3' wide. 4 Panels. Open above the glass rear wall.</p>					

S/No	Description of item (with brief specification and reference to Book of specification)	Qty	Unit	In Figures In USD/ EURO	Rates in Words In USD/EURO	Amount (Rs)
2.1	The back glass wall as well as the fittings shall be approved by World Squash Federation. The work has to be executed as per the specifications and to the entire satisfaction of Engineer - in - Charge. For Single Court	2	no			
2.2	For double court	2	no			
3.0	Tin Board :- Providing of 18" x 21ft. Soundboard made of MS Steel 18 gauge White Enamel Painted inclusive of wooden framework and top 2" wooden batten with game line marking as per WSF rules complete in all respect to the entire satisfaction of Engineer-in-Charge	4	no			
Total Bid Price in USD/Euro in Figures						
Total Bid Price in USD/Euro in words						

Date:

Full signature, Name & Address of the tenderer